



CE RoHS

尺寸

量程	C1	C2	C3	C4	H	H1	H2	H3	N	T	T1
Klb/inches											
50	1.25	2.88	2.00	6.00	3.25	0.19	0.44	1.00	4	3/8-24 UNF 深 0.40	1/4-18 NPT
100	2.31	3.94	3.00	6.00	5.00	0.25	0.75	1.25	4	1/2-20 UNF 深 0.80	1/2-14 NPT
200	3.00	5.94	5.00	17.00	6.63	0.25	0.87	1.50	4	3/4-16 UNF 深 0.80	1/2-14 NPT
300	3.00	5.94	5.00	17.00	7.00	0.25	1.00	1.75	6	3/4-16 UNF 深 0.80	1/2-14 NPT
500	5.56	7.94	6.00	30.00	7.75	0.50	1.26	2.00	6	1-1/4-16 UNF 深 1.40	1/2-14 NPT
750	5.97	10.94	8.00	50.00	12.00	0.50	2.00	3.00	8	1-1/2-12 UNF 深 2.00	1/2-14 NPT
1,000	5.97	10.94	8.00	50.00	12.00	0.50	2.00	3.00	8	1-1/2-12 UNF 深 2.00	1/2-14 NPT
kg/mm (由上述尺寸转换)											
22,679.6	31.8	73.2	50.8	152.4	82.6	4.8	11.2	25.4	4	3/8-24 UNF 深 10	1/4-18 NPT
45,359.2	58.7	100.1	76.2	152.4	127.0	6.4	19.1	31.8	4	1/2-20 UNF 深 22	1/2-14 NPT
90,718.5	76.2	150.9	127.0	431.8	168.4	6.4	22.1	38.1	4	3/4-16 UNF 深 22	1/2-14 NPT
136,077.7	76.2	150.9	127.0	431.8	177.8	6.4	25.4	44.5	6	3/4-16 UNF 深 22	1/2-14 NPT
226,796.2	141.2	201.7	152.4	762.0	196.9	12.7	32.0	50.8	6	1-1/4-16 UNF 深 35	1/2-14 NPT
340,194.3	151.6	277.9	203.2	1270.0	304.8	12.7	50.8	76.2	8	1-1/2-12 UNF 深 50	1/2-14 NPT
453,592.4	151.6	277.9	203.2	1270.0	304.8	12.7	50.8	76.2	8	1-1/2-12 UNF 深 50	1/2-14 NPT

技术参数

灵敏度	2.0 mV/V ± 0.25%	额定激励电压	10V (15V 最大)
零位输出	± 0.02 mV/V	绝缘阻抗	> 2 [50V DC] GΩ
非线性	< ± 0.1%	正常工作温度范围	-10°C - 50°C / 14°F - 122°F
重复性	< ± 0.030%	安全极限载荷	150% 满量程
滞后误差	< ± 0.050%	破坏极限载荷	300% 满量程
蠕变	< ± 0.030%	密封方式	密封 / IP67
输入阻抗	450 Ω ± 20	接线方式	Exc+ 红 Exc- 黑
输出阻抗	350 Ω ± 3		Sig+ 绿 Sig- 白
原材料	合金钢		屏蔽线

货号

量程	货号	毛重(kg)
50Klb.....	106DH-50Klb.....	2.0
100Klb.....	106DH-100Klb.....	5.0
200Klb.....	106DH-200Klb.....	12.0
300Klb.....	106DH-300Klb.....	15.7
500Klb.....	106DH-500Klb.....	30.0
750Klb.....	106DH-750Klb.....	78.0
1000Klb.....	106DH-1000Klb.....	82.0

可互换产品

制造商	型号
Coti Global.....	CG-94
Vishay Sensortronics.....	65094